

FELDER GROUP USA Headquarters	
USA Headquarters New Castle, Delaware Showroom	
2 Lukens Drive, Suite 100-400 New Castle, DE 19720 Tel. 866-792-5288	
FELDER®	
FELDER K 700 PCS, SPECIAL EDITION - Industrial Cabinet Saw with Sliding Table	Equipment
1x 230 V, 60 Hz, Motor Power 4.0 HP (3.0 kW)	Select one
3x 230 V, 60 Hz, Motor Power 5.5 HP (3.0 kW)	Select one
Additional Emergency Stop	Standard
Preventive Contact System – PCS®, Saw blades with a diameter of up to 315 mm lower completely in the case of danger. Larger saw blades will only partially lower. PCS® can be deactivated for the cutting of electrically conductive materials. PCS® does not replace any of the statutory protective devices. According to regulations, the machine must be operated with splitter and sawguard .	Standard
Sliding tablesaw with tilting sawblade (90°–45°), maximum cutting height of 4” (104 mm) with a 12” (315 mm) saw blade, 4800 rpm	Standard
Electronic height adjustment on saw blade, without LED display (#71)	Standard
Digital indicator on handwheel for saw tilt	Standard
Preparation for Dado tooling up to ¾” (19.5 mm) width	Standard
Cutting width 49” (1250 mm) with full table length, min. transport width 39” (1000 mm)	Standard
Micro adjustable rip fence	Standard
Overhead saw guard for 49” (1250 mm) cutting width, swings away from the working area	Standard
X-Roll Sliding Table, Anodized, Cutting Length 51” (1300 mm)	Standard
Crosscut fence 43” (1100 mm)	Standard
Working height	35”
Min. transport width	39⅜”
Extractor connection port diameter 120 mm on overhead saw guard 80 mm	Standard
Weight (with average equipment)	1100 lbs
Packed on an IPPC pallet	Standard
www.felder-group.com	